CodeMirror cheat sheet

General (Windows)

Ctrl + A	Select all
Esc	When multiple selections are present, deselect all but the primary selection
Ctrl + D	Delete line under the cursor
Ctrl + Z	Undo last change
Ctrl + Y	Redo the last undone change
Ctrl + U	Undo the last change to the selection, or if there are no selection-only changes at the top of the history, undo the last change
Alt + U	Redo the last change to the selection, or the last text change if no selection changes remain
Ctrl + Home	Move cursor to the start of the document
Ctrl + End	Move cursor to the end of the document
Alt + Left arrow	Move cursor to the start of the line
Home	Move to the start of the text on the line, or if we are already there, go to the actual start of the line (including whitespace)
Alt + Right arrow	Move cursor to the end of the line
Up arrow	Move the cursor up one line
Down arrow	Move the cursor down one line
Page Up	Move the cursor up one screen, and scroll up by the same distance
Page Down	Move the cursor down one screen, and scroll down by the same distance
Left arrow	Move the cursor one character left, going to the previous line when hitting the start of line
Right arrow	Move the cursor one character right, going to the next line when hitting the end of line
Ctrl + Left arrow	Move to the left of the group before the cursor. A group is a stretch of word characters, a stretch of punctuation characters, a newline, or a stretch of more than one whitespace character
Ctrl + Right arrow	Move to the right of the group after the cursor
Shift + Backspace	Delete the character before the cursor
Del	Delete the character after the cursor
Ctrl + Backspace	Delete to the left of the group before the cursor
Ctrl + Del	Delete to the start of the group after the cursor
Shift + Tab	Auto-indent the current line or selection
Ctrl +]	Indent the current line or selection by one indent unit
Ctrl + [	Dedent the current line or selection by one indent unit
Tab	If something is selected, indent it by one indent unit. If nothing is selected, insert a tab character
Enter	Insert a newline and auto-indent the new line
Insert	Toggle the overwrite flag
Ctrl + S	Not defined by the core library, only referred to in key maps. Intended to provide an easy way for user code to define a save command
Ctrl + F	Find
Ctrl + G	Find next
Shift + Ctrl + G	Find previous
Shift + Ctrl + F	Replace
Shift + Ctrl + R	Replace all. Not defined by the core library, but defined in the search addon (or custom client addons)

General (Mac)

Cmd + A	Select all
Ctrl + K	Emacs-style line killing. Deletes the part of the line after the cursor. If that consists only of

	whitespace, the newline at the end of the line is also deleted
Cmd + D	Delete line under the cursor
Cmd + Backspace	Delete the part of the line from the left side of the visual line the cursor is on to the cursor
Cmd + Del	Delete the part of the line from the cursor to the right side of the visual line the cursor is on
Cmd + Z	Undo last change
Shift + Cmd + Z or Cmd + Y	Redo the last undone change
Cmd + U	Undo the last change to the selection, or if there are no selection-only changes at the top of the history, undo the last change
Shift + Cmd + U	Redo the last change to the selection, or the last text change if no selection changes remain
Cmd + Up arrow or Cmd + Home	Move cursor to the start of the document
Cmd + End or Cmd + Down arrow	Move cursor to the end of the document
Control + A	Move cursor to the start of the line
Home	Move to the start of the text on the line, or if we are already there, go to the actual start of the line (including whitespace)
Control + E	Move cursor to the end of the line
Cmd + Right arrow	Move the cursor to the right side of the visual line it is on
Cmd + Left arrow	Move the cursor to the left side of the visual line it is on. If this line is wrapped, that may not be the start of the line
Up arrow or Control + P	Move the cursor up one line
Down arrow or Control + N	Move the cursor down one line
Page Up or Shift + Control + V	Move the cursor up one screen, and scroll up by the same distance
Page Down or Control + V	Move the cursor down one screen, and scroll down by the same distance
Left arrow or Control + B	Move the cursor one character left, going to the previous line when hitting the start of line
Right arrow or Control + F	Move the cursor one character right, going to the next line when hitting the end of line
Option + Left arrow	Move to the left of the group before the cursor. A group is a stretch of word characters, a stretch of punctuation characters, a newline, or a stretch of more than one whitespace character
Option + Right arrow	Move to the right of the group after the cursor
Shift + Backspace or Control + H	Delete the character before the cursor
Del or Control + D	Delete the character after the cursor
Option + Backspace	Delete up to the start of the word before the cursor
Option + D	Delete up to the end of the word after the cursor
Option + Backspace	Delete to the left of the group before the cursor
Control + Option + Backspace or Alt + Del	Delete to the start of the group after the cursor
Shift + Tab	Auto-indent the current line or selection
Cmd +]	Indent the current line or selection by one indent unit
Cmd + [	Dedent the current line or selection by one indent unit
Tab	If something is selected, indent it by one indent unit. If nothing is selected, insert a tab character
Control + T	Swap the characters before and after the cursor
Enter	Insert a newline and auto-indent the new line
Insert	Toggle the overwrite flag
Cmd + S	Not defined by the core library,

	only referred to in key maps. Intended to provide an easy way for user code to define a save command
Cmd + F	Find
Cmd + G	Find next
Shift + Cmd + G	Find previous
Cmd + Option + F	Replace
Shift + Cmd + Option + F	Replace all. Not defined by the core library, but defined in the search addon (or custom client addons)

Source: CodeMirror manual

Last modification: 1/16/2021 8:54:16 AM

More information: *defkey.com/codemirror-shortcuts*

Customize this PDF...