



CodeMirror cheat sheet

General (Windows)

| | |
|-------------------|--|
| Ctrl + A | Select all |
| Esc | When multiple selections are present, deselect all but the primary selection |
| Ctrl + D | Delete line under the cursor |
| Ctrl + Z | Undo last change |
| Ctrl + Y | Redo the last undone change |
| Ctrl + U | Undo the last change to the selection, or if there are no selection-only changes at the top of the history, undo the last change |
| Alt + U | Redo the last change to the selection, or the last text change if no selection changes remain |
| Ctrl + Home | Move cursor to the start of the document |
| Ctrl + End | Move cursor to the end of the document |
| Alt + Left arrow | Move cursor to the start of the line |
| Home | Move to the start of the text on the line, or if we are already there, go to the actual start of the line (including whitespace) |
| Alt + Right arrow | Move cursor to the end of the line |
| Up arrow | Move the cursor up one line |
| Down arrow | Move the cursor down one line |
| Page Up | Move the cursor up one screen, and scroll up by the same distance |
| Page Down | Move the cursor down one screen, and scroll down by the same distance |
| Left arrow | Move the cursor one character left, going to the previous line when hitting the start of line |
| Right arrow | Move the cursor one character right, going to the next line when hitting the end of line |
| Ctrl + Left arrow | Move to the left of the group before the cursor. A group is a stretch of word characters, a |

| | |
|--------------------|---|
| | stretch of punctuation characters, a newline, or a stretch of more than one whitespace character |
| Ctrl + Right arrow | Move to the right of the group after the cursor |
| Shift + Backspace | Delete the character before the cursor |
| Del | Delete the character after the cursor |
| Ctrl + Backspace | Delete to the left of the group before the cursor |
| Ctrl + Del | Delete to the start of the group after the cursor |
| Shift + Tab | Auto-indent the current line or selection |
| Ctrl +] | Indent the current line or selection by one indent unit |
| Ctrl + [| Dedent the current line or selection by one indent unit |
| Tab | If something is selected, indent it by one indent unit. If nothing is selected, insert a tab character |
| Enter | Insert a newline and auto-indent the new line |
| Insert | Toggle the overwrite flag |
| Ctrl + S | Not defined by the core library, only referred to in key maps. Intended to provide an easy way for user code to define a save command |
| Ctrl + F | Find |
| Ctrl + G | Find next |
| Shift + Ctrl + G | Find previous |
| Shift + Ctrl + F | Replace |
| Shift + Ctrl + R | Replace all. Not defined by the core library, but defined in the search addon (or custom client addons) |

General (Mac)

| | |
|----------|---|
| Cmd + A | Select all |
| Ctrl + K | Emacs-style line killing. Deletes the part of the line after the cursor. If that consists only of |

whitespace, the newline at the end of the line is also deleted

| | |
|--------------------------------|--|
| Cmd + D | Delete line under the cursor |
| Cmd + Backspace | Delete the part of the line from the left side of the visual line the cursor is on to the cursor |
| Cmd + Del | Delete the part of the line from the cursor to the right side of the visual line the cursor is on |
| Cmd + Z | Undo last change |
| Shift + Cmd + Z or Cmd + Y | Redo the last undone change |
| Cmd + U | Undo the last change to the selection, or if there are no selection-only changes at the top of the history, undo the last change |
| Shift + Cmd + U | Redo the last change to the selection, or the last text change if no selection changes remain |
| Cmd + Up arrow or Cmd + Home | Move cursor to the start of the document |
| Cmd + End or Cmd + Down arrow | Move cursor to the end of the document |
| Control + A | Move cursor to the start of the line |
| Home | Move to the start of the text on the line, or if we are already there, go to the actual start of the line (including whitespace) |
| Control + E | Move cursor to the end of the line |
| Cmd + Right arrow | Move the cursor to the right side of the visual line it is on |
| Cmd + Left arrow | Move the cursor to the left side of the visual line it is on. If this line is wrapped, that may not be the start of the line |
| Up arrow or Control + P | Move the cursor up one line |
| Down arrow or Control + N | Move the cursor down one line |
| Page Up or Shift + Control + V | Move the cursor up one screen, and scroll up by the same distance |

Page Down or Control + V

Move the cursor down one screen, and scroll down by the same distance

Left arrow or Control + B

Move the cursor one character left, going to the previous line when hitting the start of line

Right arrow or Control + F

Move the cursor one character right, going to the next line when hitting the end of line

Option + Left arrow

Move to the left of the group before the cursor. A group is a stretch of word characters, a stretch of punctuation characters, a newline, or a stretch of more than one whitespace character

Option + Right arrow

Move to the right of the group after the cursor

Shift + Backspace or Control + H

Delete the character before the cursor

Del or Control + D

Delete the character after the cursor

Option + Backspace

Delete up to the start of the word before the cursor

Option + D

Delete up to the end of the word after the cursor

Option + Backspace

Delete to the left of the group before the cursor

Control + Option + Backspace or Alt + Del

Delete to the start of the group after the cursor

Shift + Tab

Auto-indent the current line or selection

Cmd +]

Indent the current line or selection by one indent unit

Cmd + [

Dedent the current line or selection by one indent unit

Tab

If something is selected, indent it by one indent unit. If nothing is selected, insert a tab character

Control + T

Swap the characters before and after the cursor

Enter

Insert a newline and auto-indent the new line

Insert

Toggle the overwrite flag

Cmd + S

Not defined by the core library,

only referred to in key maps.
Intended to provide an easy way
for user code to define a save
command

| | |
|-----------------------------|--|
| Cmd + F | Find |
| Cmd + G | Find next |
| Shift + Cmd + G | Find previous |
| Cmd + Option + F | Replace |
| Shift + Cmd + Option + F | Replace all. Not defined by the core library, but defined in the search addon (or custom client addons) |

Source: CodeMirror manual

Last modification: 2021/1/16 08:54:16

More information: defkey.com/eu/codemirror-shortcuts

[Customize this PDF...](#)