

Manjaro Linux cheat sheet

Kernel

These shortcuts can be used for recovering from an unresponsive system or debugging.

To use these shortcuts, they must first be activated with either `sysctl kernel.sysrq=1` or `echo "1" > /proc/sys/kernel/sysrq`

Alt + Sys Rq + R	Unraw - Take control of keyboard back from X.
Alt + Sys Rq + E	Terminate - Send SIGTERM to all processes, allowing them to terminate gracefully
Alt + Sys Rq + I	Kill - Send SIGKILL to all processes, forcing them to terminate immediately
Alt + Sys Rq + S	Sync - Flush data to disk
Alt + Sys Rq + U	Unmount - Unmount and remount all file systems read-only
Alt + Sys Rq + B	Reboot

Terminal: Virtual console

Ctrl + Alt + Del	Reboots Computer (specified by the symlink <code>/usr/lib/systemd/system/ctrl-alt-del.target</code>)
Alt + F1	(F2, F3, ...) Switch to n-th virtual console
Alt + Left arrow	Switch to previous virtual console
Alt + Right arrow	Switch to next virtual console
Scroll Lock	When Scroll Lock is activated, input/output is locked
Shift + Page Up / Down	Scroll the console buffer up/down
Ctrl + C	Kill the current task
Ctrl + D	Insert an EOF
Ctrl + Z	Pause the current Task

Terminal: Readline

Ctrl + L	Clear the screen
Cursor Movement	
Ctrl + B	Move cursor one character to the left

Ctrl + F Move cursor one character to the right

Alt + B Move cursor one word to the left

Alt + F Move cursor one word to the right

Ctrl + A Move cursor to start of the line

Ctrl + E Move cursor to end of the line

Copy & Paste

Ctrl + U Cut everything from line start to cursor

Ctrl + K Cut everything from the cursor to end of the line

Alt + D Cut the current word after the cursor

Ctrl + W Cut the current word before the cursor

Ctrl + Y Paste the previous cut text

Alt + Y Paste the second latest cut text

Alt + Ctrl + Y Paste the first argument of the previous command

Alt + ./_ Paste the last argument of the previous command

History

Ctrl + P Move to the previous line

Ctrl + N Move to the next line

Ctrl + S Search

Ctrl + R Reverse search

Ctrl + J End search

Ctrl + G Abort search (restores original line)

Alt + R Restores all changes made to line

Completion

Tab Auto-complete a name

Alt + ? List all possible completions

Alt + * Insert all possible completions

X11

Ctrl + Alt + F1 Switch to n-th virtual console

Shift + Insert or Right click Paste text from the PRIMARY buffer

By default, Qt maps Shift+Insert to CLIPBOARD

instead of the PRIMARY buffer

Source: Manjaro Linux

Last modification: 3/15/2023 3:08:23 PM

More information: defkey.com/manjaro-linux-20-shortcuts

[Customize this PDF...](#)